

PAL[®] BY MICROAIRE



The Preeminent Power-Assisted Liposuction System by **MICROAIRE**

PAL Handpiece | PAL-750

PAL is a powerful precision instrument designed for small or large volume fat extraction, body contouring, and fat harvesting.

Weight	1.1 lb (0.5 kg)
Dimensions	8" x 1" x 1.5" (20.3 x 2.5 x 3.8 cm)
Stroke Length	3.2 mm
Maximum Speed	4,000-5,000 cycles/min

PAL Console | 5020

The Console can control two PAL handpieces at once. Speed can be controlled on the touchscreen interface or on the Handpiece.

Dimensions	12" x 14" x 6" (30.5 x 35.6 x 15.2 cm)
Electrical	300 W, 100-240 V, 50/60 Hz



PAL Cable | 5006-PAL



PAL Tubing | PAL-1200
Length 12 ft. (3.66 m)

The Value of PAL

- 35% reduction in procedure time.*¹
- 49% less surgeon fatigue* for a safer and more precise procedure.¹
- 2-year warranty included with the PAL-750.
- 5 years of complimentary loaner equipment during repairs.

***"We are in the golden age of liposuction thanks to PAL.
Grateful to have MicroAire on my side." - Dr. William Rahal***

PAL Infiltration Pump | INF-KIT

The PAL Infiltration Pump is the only infiltration pump that can be activated from the PAL Handpiece.



Pump Type	Peristaltic
Maximum Flow Rate	1,150 mL/min
Dimensions	11.2" x 10.1" x 5.1" (29 x 26 x 13 cm)



Dual Foot-switch Connections

Three-way Selector

Pump Speed Control

"I have been using the great MicroAire PAL for decades. It just keeps on working year after year. Very few medical instruments can compare."

– Dr. Richard Sadove

*Compared to traditional manual liposuction.



PAL Infiltration Tubing
PAL-INF-1600

1. Katz BE, Bruck MC, Coleman WP. The Benefits of Powered Liposuction Versus Traditional Liposuction: A Paired Comparison Analysis. 2001. Dermatol Surg; 27:863-967. Power-Assisted Liposuction (PAL) or Suction Assisted Liposuction (SAL). 2011.

Indications and claims are for USA only.

PAL LipoTower® & LipoFilter®

PAL LipoTower (USA and Canada Only) | ASP-1021

The PAL LipoTower is a powerful surgical cart with strong, reliable pumps for both infiltration and aspiration. It includes a touchscreen interface and integrated PAL control system.

Vacuum Pump	Dual 1/4-Horsepower, Rotary Vane
Vacuum Pressure	0–29 in/Hg (0–736 mm Hg) at Sea Level
Infiltration Pump	Peristaltic
Infiltration Flow Rate	50–600 ml/min
Footprint	2' x 2' (0.6 m x 0.6 m)
Electrical	120 V, 60 Hz (UL-Listed)



LipoFilter ASP-CAN-2S (+ Toomey Syringe) ASP-CAN-NT (Without Syringe)

The LipoFilter is a large-volume (2,500 ml) gravity-decant fat processing system. It is sterile-packed, single-use, and works with any liposuction system.

"PAL has been [the] only suction I need for all my body contouring cases. My go-to essential instrument."

– Dr. Andrew Cohen

MicroAire Surgical Instruments 3590 Grand Forks Boulevard Charlottesville, VA 22911
USA 800 722 0822 or +434 975 8000

©2024 MicroAire Surgical Instruments, LLC
All rights reserved. LIT-PAL-SYSTEM Rev A



A Marmon |
Berkshire Hathaway
Company

VERKAUF

TapMed

Medizintechnik Handels GmbH
Gewerbepark 10
34317 Habichtswald-Ehlen
GERMANY
Tel. +49 (0)5606 53060-0
Fax +49 (0)5606 53060-44

www.tapmed.de